



SEMIN ANCIENS FONDS

RENOVATION PASTE FILLER INTERIOR - EXTERIOR

TECHNICAL DEFINITION

Ready mixed filler for smoothing irregular substrates on interior and exterior walls.

Particularly suitable for wet rooms (kitchens, bathrooms, toilets).

COMPOSITION AND APPEARANCE

Emulsion resin containing calcium carbonate, water, rheological agent and various additives.

The resulting paste is off-white.

ACCEPTED SUBSTRATES

- Earthenware blocks.
- Cement render.
- Sanded and primed wood.
- RPE (Heavy plastic covering).
- Fibreglass.
- Plaster board.
- Old paintwork.
- Plaster blocks.
- Concrete.
- Textured finish.

COVERING

- Plaster base finishing filler.
- Matt paint.
- Paste filler.

DOCUMENTS TO CONSULT

- Filler in conformity with standard NFT 30 608.
- DTU 59.1: Paintwork.
- CEBTP Report N° 2352.6.740/1: Permeable to water vapor. Measurement of adherence-cohesion before and after climatic cycles.

TECHNICAL CHARACTERISTICS

- Particle size: up to 0.6 mm.
- Adherence: in conformity with NFT 30 608.
- pH: neutral.
- Dry extract: 80 %.

PACKING

375 g tubes.
1.5 – 5 and 15 kg pails.

STORAGE

6 months in unopened original packing protected from damp and strong heat.

APPLICATION

PRECAUTIONS FOR USE

The application and drying temperature must be between 8° C and 35° C.

Do not apply on damp substrates.

PREPARATION OF SURFACES

Substrates must be in conformity with DTU 59.1, i.e. they must be clean, dry, hard and free of dust and of any traces of formwork release oil.

APPLICATION

Application is to be carried out using a float or a filling knife.

APPLICATION THICKNESS

Up to 5 mm in one coat.

CONSUMPTION

Approximately 1.5 kg/m²/mm thickness.

DRYING TIME

Depends on the atmospheric conditions, the type of substrate and the application thickness.

As a general rule, for 5 mm thickness, SEMIN ANCIENS FONDS dries in between 24 and 36 hours.

MULTI-PURPOSE RENOVATION PASTE FILLER



SEMIN ANCIENS FONDS is a general-purpose renovation filler suitable for every interior and exterior substrate, and wet rooms.

ADVANTAGES

- Very high filling capacity
- Easy to apply indoors or outdoors.
- Ideal product for covering old painted fibreglass.

APPLICATION TIP

SEMIN ANCIENS FONDS is particularly recommended for renovating wet rooms thanks to its formulation based on highly water resistant resin.



DAMP ROOM



AFNOR classification nft 36.005.
Family IV – Class 4 b.
Conforms to DTU 42.1.

Replace
HERCULE

